

TECHICAL DATA SHEET

PRODUCT DESCRIPTION	: CAUSTIC CALCINED MAGNESIA
PRODUCT BRAND NAME	: ALFAMAG
APPLICATION	: ANIMAL FEED - AGRICULTURE - FERTILIZERS
ORIGIN	: GREEK

CHEMICAL COMPOSITION	PHYSICAL CHARACTERISTICS																																																						
<table style="width: 100%; border-collapse: collapse;"> <tr> <td colspan="4" style="text-align: center;">Non Ignited</td> </tr> <tr> <td style="width: 15%;">MgO</td> <td style="width: 25%;">86,5 - 90,0 %</td> <td style="width: 15%;">88,70</td> <td style="width: 45%;">% typ.</td> </tr> <tr> <td>Mg</td> <td>52,1 % min</td> <td>53,40</td> <td>% typ.</td> </tr> <tr> <td colspan="4" style="text-align: center;">Loss Free (XRF)</td> </tr> <tr> <td>MgO</td> <td>90,0 - 91,0 %</td> <td>90,50</td> <td>% typ.</td> </tr> <tr> <td>SiO₂</td> <td>3,0 - 6,0 %</td> <td>5,00</td> <td>% typ.</td> </tr> <tr> <td>CaO</td> <td>2,0 - 4,3 %</td> <td>3,70</td> <td>% typ.</td> </tr> <tr> <td>Fe₂O₃</td> <td>0,4 - 0,8 %</td> <td>0,60</td> <td>% typ.</td> </tr> <tr> <td>Al₂O₃</td> <td>0,10 % max</td> <td>0,08</td> <td>% typ.</td> </tr> <tr> <td>MnO</td> <td>0,02 % max</td> <td>0,01</td> <td>% typ.</td> </tr> <tr> <td>SO₃</td> <td>0,20 % max</td> <td>0,05</td> <td>% typ.</td> </tr> <tr> <td>P₂O₅</td> <td>0,10 % max</td> <td>0,06</td> <td>% typ.</td> </tr> </table>	Non Ignited				MgO	86,5 - 90,0 %	88,70	% typ.	Mg	52,1 % min	53,40	% typ.	Loss Free (XRF)				MgO	90,0 - 91,0 %	90,50	% typ.	SiO₂	3,0 - 6,0 %	5,00	% typ.	CaO	2,0 - 4,3 %	3,70	% typ.	Fe₂O₃	0,4 - 0,8 %	0,60	% typ.	Al₂O₃	0,10 % max	0,08	% typ.	MnO	0,02 % max	0,01	% typ.	SO₃	0,20 % max	0,05	% typ.	P₂O₅	0,10 % max	0,06	% typ.	<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 15%;">Sizing</td> <td>: Granular (0-1.5 mm) Granular (0.2-1.5 mm) Granular (0-0.2 mm) Milled d90 <75µm Milled d90 <45µm</td> </tr> <tr> <td>L.O.I.</td> <td>: 4.00% max</td> </tr> <tr> <td>Moisture</td> <td>: 0,5% max</td> </tr> </table>	Sizing	: Granular (0-1.5 mm) Granular (0.2-1.5 mm) Granular (0-0.2 mm) Milled d90 <75µm Milled d90 <45µm	L.O.I.	: 4.00% max	Moisture	: 0,5% max
Non Ignited																																																							
MgO	86,5 - 90,0 %	88,70	% typ.																																																				
Mg	52,1 % min	53,40	% typ.																																																				
Loss Free (XRF)																																																							
MgO	90,0 - 91,0 %	90,50	% typ.																																																				
SiO₂	3,0 - 6,0 %	5,00	% typ.																																																				
CaO	2,0 - 4,3 %	3,70	% typ.																																																				
Fe₂O₃	0,4 - 0,8 %	0,60	% typ.																																																				
Al₂O₃	0,10 % max	0,08	% typ.																																																				
MnO	0,02 % max	0,01	% typ.																																																				
SO₃	0,20 % max	0,05	% typ.																																																				
P₂O₅	0,10 % max	0,06	% typ.																																																				
Sizing	: Granular (0-1.5 mm) Granular (0.2-1.5 mm) Granular (0-0.2 mm) Milled d90 <75µm Milled d90 <45µm																																																						
L.O.I.	: 4.00% max																																																						
Moisture	: 0,5% max																																																						
<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 15%;"></td> <td style="width: 15%;">Cl⁻</td> <td style="width: 15%;">< 200</td> <td style="width: 55%;">ppm</td> </tr> <tr> <td></td> <td>Pb</td> <td>< 4</td> <td>ppm</td> </tr> <tr> <td></td> <td>Cd</td> <td>< 0.1</td> <td>ppm</td> </tr> <tr> <td></td> <td>As</td> <td>< 1</td> <td>ppm</td> </tr> <tr> <td></td> <td>Hg</td> <td><0.05</td> <td>ppm</td> </tr> <tr> <td></td> <td>F</td> <td><250</td> <td>ppm</td> </tr> <tr> <td></td> <td>Dioxins (PCDDs+PCDFs)</td> <td><0,1</td> <td>ng/kg</td> </tr> <tr> <td></td> <td>Dioxin-like PCBs</td> <td><0,05</td> <td>ng/kg</td> </tr> <tr> <td></td> <td>Non Dioxin-like PCBs</td> <td><0,5</td> <td>µg/kg</td> </tr> </table>		Cl⁻	< 200	ppm		Pb	< 4	ppm		Cd	< 0.1	ppm		As	< 1	ppm		Hg	<0.05	ppm		F	<250	ppm		Dioxins (PCDDs+PCDFs)	<0,1	ng/kg		Dioxin-like PCBs	<0,05	ng/kg		Non Dioxin-like PCBs	<0,5	µg/kg	<table style="width: 100%; border-collapse: collapse;"> <tr> <th style="text-align: center;">ANALYSIS METHODS</th> </tr> <tr> <td><i>Chemical analysis by XRF</i></td> </tr> <tr> <td><i>Loss on Ignition by heating at 1000° C</i></td> </tr> <tr> <td><i>Moisture by heating at 120° C</i></td> </tr> <tr> <td><i>Sizing by mechanical sieve shaker/laser diffraction</i></td> </tr> <tr> <td><i>Cd/Pb/As/Hg/F/Cl/Dioxins analysed in external labs</i></td> </tr> </table>	ANALYSIS METHODS	<i>Chemical analysis by XRF</i>	<i>Loss on Ignition by heating at 1000° C</i>	<i>Moisture by heating at 120° C</i>	<i>Sizing by mechanical sieve shaker/laser diffraction</i>	<i>Cd/Pb/As/Hg/F/Cl/Dioxins analysed in external labs</i>												
	Cl⁻	< 200	ppm																																																				
	Pb	< 4	ppm																																																				
	Cd	< 0.1	ppm																																																				
	As	< 1	ppm																																																				
	Hg	<0.05	ppm																																																				
	F	<250	ppm																																																				
	Dioxins (PCDDs+PCDFs)	<0,1	ng/kg																																																				
	Dioxin-like PCBs	<0,05	ng/kg																																																				
	Non Dioxin-like PCBs	<0,5	µg/kg																																																				
ANALYSIS METHODS																																																							
<i>Chemical analysis by XRF</i>																																																							
<i>Loss on Ignition by heating at 1000° C</i>																																																							
<i>Moisture by heating at 120° C</i>																																																							
<i>Sizing by mechanical sieve shaker/laser diffraction</i>																																																							
<i>Cd/Pb/As/Hg/F/Cl/Dioxins analysed in external labs</i>																																																							
PACKAGING	Big-Bags of about 1.000 Kgs each with inner liner Paper-Bags of about 25 Kgs each with inner liner																																																						
SOURCE	Caustic Calcined Magnesite produced from the high quality cryptocrystalline deposits of North Euboea Island/Greece, using multiple hearth furnace calcination																																																						
STORAGE	The product must be stored in a clean, dry storage area and protected from moisture																																																						
Issue Date: 27.06.2016																																																							

DISCLAIMER:

The data contained in this TDS is solely for informational purposes.
The figures included are not to be considered as specifications and may change without notice.